

## Table of Contents

|  |           |
|--|-----------|
| <b>Preface . . . . .</b>   | <b>xi</b> |
| <b>Chapter 1. Mechatronics Systems Based on CAD/CAM . . . . .</b>  |           |
| Fusaomi NAGATA, Yukihiro KUSUMOTO, Keigo WATANABE and Maki K. HABIB  |           |
| 1.1. Introduction . . . . .  | 1         |
| 1.2. Five-axis NC machine tool with a tilting head . . . . .   | 1         |
| 1.3. Three-axis NC machine tool with a rotary unit . . . . .   | 4         |
| 1.3.1. Introduction . . . . .  | 4         |
| 1.3.2. Post-processor for a three-axis NC machine tool with<br>a rotary unit . . . . .                     | 5         |
| 1.3.3. Experiment . . . . .  | 7         |
| 1.4. Articulated-type industrial robot . . . . .   | 8         |
| 1.4.1. Introduction . . . . .  | 8         |
| 1.4.2. For sanding a wooden workpiece . . . . .  | 9         |
| 1.4.3. For mold finishing . . . . .  | 16        |
| 1.5. Desktop Cartesian-type robot . . . . .  | 21        |
| 1.5.1. Background . . . . .  | 21        |
| 1.5.2. Cartesian-type robot . . . . .  | 22        |
| 1.5.3. Design of weak coupling control between force feedback<br>loop and position feedback loop . . . . . | 23        |
| 1.5.4. Frequency characteristic of force control system . . . . .  | 24        |
| 1.5.5. Finishing experiment of an LED lens mold . . . . .  | 25        |
| 1.6. Conclusions . . . . .   | 26        |
| 1.7. Bibliography . . . . .  | 27        |

|   |            |
|---|------------|
| <b>Chapter 2. Modeling and Control of Ionic Polymer–Metal Composite Actuators for Mechatronics Applications . . . . .</b> | <b>29</b>  |
| Andrew MCDAID, Kean AW and Sheng Q. XIE   |            |
| 2.1. Introduction . . . . .   | 29         |
| 2.2. Electromechanical IPMC model . . . . .   | 33         |
| 2.2.1. Nonlinear electric circuit . . . . .   | 35         |
| 2.2.2. Electromechanical coupling . . . . .   | 38         |
| 2.2.3. Mechanical beam model . . . . .  | 39         |
| 2.2.4. Parameter identification and results . . . . .   | 40         |
| 2.3. IPMC stepper motor . . . . .   | 44         |
| 2.3.1. Mechanical design . . . . .  | 45         |
| 2.3.2. Model integration and simulation . . . . .   | 46         |
| 2.3.3. Experimental validation . . . . .  | 46         |
| 2.3.4. Extension to four IPMCs . . . . .  | 48         |
| 2.4. Robotic rotary joint . . . . .   | 49         |
| 2.4.1. Mechanical design . . . . .  | 50         |
| 2.4.2. Control system . . . . .   | 50         |
| 2.4.3. System parameter tuning . . . . .  | 51         |
| 2.4.4. Experimental tuning results . . . . .  | 55         |
| 2.4.5. Gain schedule nonlinear controller . . . . .   | 58         |
| 2.4.6. Gain schedule vs. PID controller . . . . .   | 60         |
| 2.5. Discussions . . . . .  | 63         |
| 2.6. Concluding remarks . . . . .   | 63         |
| 2.7. Bibliography . . . . .   | 64         |
| <b>Chapter 3. Modeling and Simulation of Analog Angular Sensors for Manufacturing Purposes . . . . .</b>                  | <b>69</b>  |
| João FIGUEIREDO   |            |
| 3.1. Introduction . . . . .   | 69         |
| 3.2. Pancake resolver model . . . . .   | 73         |
| 3.2.1. Description . . . . .  | 73         |
| 3.2.2. Mathematical model . . . . .   | 75         |
| 3.3. Simulation and experimental results . . . . .  | 94         |
| 3.3.1. Performance of the overall model . . . . .   | 94         |
| 3.3.2. Manufacturer correction tools . . . . .  | 95         |
| 3.4. Conclusions . . . . .  | 99         |
| 3.5. Acknowledgment . . . . .   | 99         |
| 3.6. Bibliography . . . . .   | 99         |
| <b>Chapter 4. Robust Control of Atomic Force Microscopy . . . . .</b>   | <b>103</b> |
| Bilin AKSUN GÜVENÇ, Serkan NECİPOĞLU, Burak DEMİREL and Levent GÜVENÇ   |            |
| 4.1. Introduction . . . . .   | 103        |

|  |            |
|--|------------|
| <b>4.2. Repetitive control of the vertical direction motion . . . . .</b>                | <b>104</b> |
| 4.2.1. Tapping mode AFM system model . . . . .   | 106        |
| 4.2.2. Repetitive control basics. . . . .  | 108        |
| 4.2.3. Mapping mixed sensitivity specifications into controller parameter space. . . . . | 110        |
| 4.2.4. Repetitive control features of COMES . . . . .                                    | 111        |
| 4.2.5. Robust repetitive controller design using the COMES toolbox . . . . .             | 113        |
| 4.2.6. Simulation results for the vertical direction . . . . .                           | 115        |
| <b>4.3. MIMO disturbance observer control of the lateral directions. . . . .</b>         | <b>117</b> |
| 4.3.1. The piezotube and the experimental setup . . . . .                                | 119        |
| 4.3.2. MIMO disturbance observer . . . . .   | 122        |
| 4.3.3. Disturbance observer design for the piezotube and experimental results . . . . .  | 124        |
| <b>4.4. Concluding remarks. . . . .</b>  | <b>128</b> |
| <b>4.5. Acknowledgments. . . . .</b>   | <b>129</b> |
| <b>4.6. Bibliography . . . . .</b>   | <b>130</b> |
| <br><b>Chapter 5. Automated Identification . . . . .</b>                                 | <br>133    |
| Hiroo WAKAUMI  |            |
| 5.1. Introduction . . . . .  | 133        |
| 5.2. Serial binary barcode . . . . .   | 134        |
| 5.2.1. Identification technology for serial binary barcodes . . . . .                    | 136        |
| 5.2.2. Requirements for serial binary barcode identification . . . . .                   | 139        |
| 5.2.3. Decoding for identification . . . . .   | 139        |
| 5.3. Two-dimensional binary barcode . . . . .  | 140        |
| 5.3.1. Scanning technology of the 2D barcode . . . . .                                   | 142        |
| 5.3.2. Multi-line scan based on time-sharing laser light emission . . . . .              | 144        |
| 5.4. Ternary barcode . . . . .   | 149        |
| 5.4.1. Dual-threshold method. . . . .  | 150        |
| 5.4.2. Envelope differential composite method . . . . .                                  | 155        |
| 5.4.3. Fixed-period delay method . . . . .   | 158        |
| 5.5. RFID . . . . .  | 160        |
| 5.5.1. Electromagnetic induction technology . . . . .                                    | 161        |
| 5.5.2. Microwave transmission technology . . . . .                                       | 162        |
| 5.6. Application examples . . . . .  | 163        |
| 5.7. Concluding remarks. . . . .   | 164        |
| 5.8. Acknowledgments. . . . .  | 164        |
| 5.9. Bibliography . . . . .  | 165        |
| <br><b>Chapter 6. An Active Orthosis for Gait Rehabilitation . . . . .</b>               | <br>169    |
| Shahid HUSSAIN and Sheng Q. XIE  |            |
| 6.1. Introduction . . . . .  | 169        |

|   |            |
|---|------------|
| 6.1.1. Gait rehabilitation . . . . .                                    | 169        |
| 6.1.2. Rehabilitation robotics . . . . .                                | 170        |
| 6.1.3. Biomechanics of gait . . . . .                                   | 172        |
| 6.1.4. Robot-assisted gait rehabilitation: a review . . . . .           | 174        |
| 6.1.5. Gait training strategies: a review . . . . .                     | 176        |
| 6.2. Compliant active orthosis design . . . . .                         | 178        |
| 6.2.1. Design criteria. . . . .   | 179        |
| 6.2.2. Active orthosis components. . . . .                              | 179        |
| 6.3. Modeling . . . . .   | 182        |
| 6.3.1. PMA dynamic modeling. . . . .                                    | 182        |
| 6.3.2. Interaction force estimation . . . . .                           | 184        |
| 6.4. Control . . . . .  | 184        |
| 6.5. Simulation results . . . . .                                       | 187        |
| 6.6. Conclusions . . . . .  | 189        |
| 6.7. Acknowledgment . . . . .   | 189        |
| 6.8. Bibliography . . . . .   | 190        |
| <b>Chapter 7. Intelligent Assistive Knee Exoskeleton . . . . .</b>      | <b>195</b> |
| Mervin CHANDRAPAL, Xiaoqi CHEN and Wenhui WANG                          |            |
| 7.1. Introduction . . . . .   | 195        |
| 7.1.1. Background on assistive devices . . . . .                        | 195        |
| 7.1.2. Lower extremity AR devices . . . . .                             | 197        |
| 7.2. Overview of knee exoskeleton system . . . . .                      | 202        |
| 7.3. Modeling and control of pneumatic artificial muscle (PAM). . . . . | 205        |
| 7.3.1. Background . . . . .   | 205        |
| 7.3.2. Characteristic of the PAM. . . . .                               | 206        |
| 7.3.3. Models from literature . . . . .                                 | 207        |
| 7.3.4. Model used. . . . .  | 209        |
| 7.4. Modeling of high-speed on/off solenoid valve . . . . .             | 211        |
| 7.4.1. Experimental validation of high-speed valve flow rate . . . . .  | 213        |
| 7.5. Self-organizing fuzzy control . . . . .                            | 214        |
| 7.5.1. Introduction to fuzzy control . . . . .                          | 214        |
| 7.5.2. Fuzzy control system for PAM . . . . .                           | 215        |
| 7.5.3. Introduction to self-organizing fuzzy controllers . . . . .      | 220        |
| 7.5.4. Practical implementation . . . . .                               | 221        |
| 7.6. Surface electromyography . . . . .                                 | 224        |
| 7.6.1. Origins of surface electromyography (sEMG) signals . . . . .     | 224        |
| 7.6.2. sEMG signal acquisition and conditioning . . . . .               | 225        |
| 7.6.3. Relating sEMG to muscle force . . . . .                          | 227        |
| 7.7. Hardware implementation . . . . .                                  | 229        |
| 7.8. Concluding remarks. . . . .  | 231        |

Table of Contents ix

|                                  |            |
|----------------------------------|------------|
| 7.9. Acknowledgment . . . . .    | 232        |
| 7.10. Bibliography . . . . .     | 232        |
| <b>List of Authors . . . . .</b> | <b>239</b> |
| <b>Index . . . . .</b>           | <b>241</b> |