

Index

A

airplane, 4
airship, 4
analog complementary filter, 79
armature current, 133
artificial vision, 41
autonomous aircraft, 301

B

bounded control, 59
brushless DC motor, 133

C

C-Plane UAV, 79
camera calibration, 173
computer vision, 191
Coriolis
 forces, 157
 matrix, 256

D

delta UAV, 115
direct visual servoing, 169
dynamic model, 6, 79, 115
 PVTOL aircraft, 24
dynamic uncertainty, 154

E

eight-rotor
 rotorcraft, 238
 UAV, 249
embedded
 flight system, 41

saturation functions, 21

saturations, 25
system, 79, 115
Euler-Lagrange
 approach, 9, 181
 formulation, 115
extended Kalman filter, 269

F

flapping-wing UAV, 5
flight plan, 301

G

genetic algorithms (GAs), 160
GPS (Global Positioning System), 168

H

homemade IMU, 79
homogenous transformation approach, 175
homography, 174
horizontal flight, 79
hover flight, 79
hovering platforms, 153

I

image-based visual servoing, 171
improving attitude stabilization, 133
IMU (inertial measurement unit), 168
indirect visual servoing, 169
inertial measurement unit (IMU), 162
inertial navigation, 286

- inner-outer loop controller, 41
- K**
 - Kalman filters, 266
 - keypoints matching algorithm, 245
- L**
 - Levenberg-Marquardt (LM), 177
 - linear
 - control, 79
 - Kalman filter, 266
 - linear matrix inequalities (LMIs), 160
 - longitudinal dynamics, 79
 - Lucas-Kanade approach, 247
- M**
 - Matlab SimulinkTM, 160
 - mini-rotorcraft UAV, 153
- N**
 - Newton-Euler
 - approach, 7
 - equations, 79
 - nonlinear control, 41, 79, 191
 - PVTOL aircraft, 21
 - nonlinear dynamics, 59
- O**
 - object detection, 191
 - optic flow, 210
 - optical flow (OF), 195, 237, 246
 - optical flow-based control, 245
 - optimal trajectories, 301
- P**
 - parametric uncertainty, 154
 - perspective of n -points approach, 177
 - plane-pose-based approach, 179
 - pose estimation, 177
 - position-image visual servoing, 172
 - pulse wide modulators (PWMs), 162
 - PVTOL aircraft
 - control strategies, 33
 - nonlinear control, 25
- Q**
 - quad-rotor UAV, 133
- quaternion approach, 10
- R**
 - RANdom SAmple Consensus (RANSAC), 241
 - robot localization, 285
 - robust
 - control design, 153, 158
 - stability analysis, 154
 - rotational
 - dynamics, 79
 - subsystem model, 255
- S**
 - Scale Invariant Features Tracking (SIFT), 241, 245
 - sensor fusion, 191
 - single
 - rotor configuration, 2
 - tilting rotor, 115
 - singular value decomposition (SVD), 241
 - spherical simplex sigma-point Kalman filters, 278
 - stereo vision, 237
 - structure from motion, 212
- T**
 - T-Plane UAV, 115
 - tail-sitter UAV, 79
 - three-dimensional localization, 265
 - tilting rotors, 59, 115
 - tracking, 191
 - transition maneuver, 79
 - translational dynamics, 79
 - triple tilting rotor, 115
 - twin rotor configuration, 3
 - two-plane calibration approach, 173, 185
- U**
 - unmanned aerial vehicles (UAV), 1, 79
 - unscented Kalman filter, 270
- V**
 - visual servoing, 168
- VTOL**
 - aircraft, 41, 191
 - rotorcraft, 59
 - vehicle, 79, 115