
Contents

Preface	xi
Introduction	xiii
Chapter 1. State of the Art	1
1.1. Motivation from the microstructure	1
1.2. Building bricks	6
1.2.1. Criteria	7
1.2.2. Isotropic hardening rules	12
1.2.3. Kinematic hardening rules (KHR)	17
1.2.4. Plastic modulus	19
1.2.5. Viscosity	24
1.3. Scale transition rules	27
1.3.1. General remarks on scale transition rules	27
1.3.2. Scale transition rules for the MM model	29
1.4. Large deformation	30
1.5. Brief history of the MM models	32
Chapter 2. Model Formulation	35
2.1. Thermodynamic framework	35
2.2. Model with various mechanisms and various criteria: the 2M2C model	37
2.3. Model with various mechanisms and one criterion: the 2M1C model	39
2.4. Comparison with the unified model	40

2.5. Isotropic hardening rules	41
2.5.1. Isotropic hardening for models with various mechanisms and one criterion	41
2.5.2. Isotropic hardening for models with various mechanisms and various criteria	43
2.6. Kinematic hardening rules	45
2.6.1. KHR: models with various mechanisms and various criteria	45
2.6.2. KHR: models with various mechanisms and one criterion	46
2.7. Computation of the inelastic multipliers	46
2.7.1. Flow rate for the 2M1C model	47
2.7.2. Flow rates for the 2M2C model	47
Chapter 3. Typical MM Responses	51
3.1. Some MM model variants	51
3.1.1. Initial MM models	51
3.1.2. Updated 2M1C models after [TAL 06]	53
3.1.3. Updated MM models after [SAÏ 07]	53
3.1.4. A general nMnC model	54
3.1.5. Generalization of the 2M1C model	56
3.2. Creep–plasticity interaction	56
3.3. Rate sensitivity for the 2M2C model	58
3.4. Stabilized behavior of viscoplastic 2M1C model	59
3.5. Closed-form solution for ratcheting behavior of the 2M2C model: case of linear kinematic hardening rules	60
3.6. Ratcheting for 2M1C model	64
3.7. Ratcheting behavior of the 10M10C model	67
3.8. Extra-hardening under non-proportional loading	69
3.9. Static recovery effect	72
Chapter 4. Comparison with Experimental Databases	77
4.1. Inconel 718	79
4.1.1. Context of the case study	79
4.1.2. Particular model features	79
4.1.3. Numerical results	79

4.2. Deformation mechanisms of Ni–Ti shape memory alloy	80
4.2.1. Context of the case study	80
4.2.2. Particular model features	82
4.2.3. Numerical results	82
4.3. N18 alloy	83
4.3.1. Context of the case study	83
4.3.2. Particular model features	84
4.3.3. Numerical results	85
4.4. Carbon steel CS1026	87
4.4.1. Context of the case study	87
4.4.2. Particular model features	87
4.4.3. Numerical results	88
4.5. Thermo-mechanical behavior of 55NiCrMoV7	89
4.5.1. Context of the case study	89
4.5.2. Particular model features	90
4.5.3. Numerical results	91
4.6. 2017 Aluminum alloy	94
4.6.1. 2017A, [SAI 12]	94
4.6.2. 2017A, [TAL 15]	97
4.7. 304 austenitic stainless steel	101
4.7.1. 304SS at room temperature [HAS 08]	101
4.7.2. 304SS at room temperature [TAL 11]	102
4.7.3. 304SS at 350°C [TAL 14]	105
4.7.4. 304SS at room temperature [HAS 94a], 2M1C-3M1C	107
4.7.5. 304SS at room temperature [HAS 08, TAL 10], 2M1C-3M1C	112
4.8. 316 austenitic stainless steel	116
4.8.1. 316SS at room temperature [POR 00]	116
4.8.2. 316SS at room temperature [TAL 15]	119
4.8.3. 316SS at 350°C [TAL 13b, TAL 14]	121
4.8.4. 316SS at room temperature [POR 00], 3M1C model	123
4.9. Recrystallized Zirconium alloy 4 [PRI 08]	124
4.9.1. Context of the case study	124
4.9.2. Particular model features	125
4.9.3. Numerical results	126

4.10. Semi-crystalline polymers [REG 09b]	126
4.10.1. Context of the case study	126
4.10.2. Particular model features	128
4.10.3. Numerical results	128
4.11. Glassy polymers [JER 14]	131
4.11.1. Context of the case study	131
4.11.2. Particular model features	132
4.11.3. Numerical results	133
4.12. Copper-zinc alloy CuZn27 [TAL 15]	136
4.12.1. Context of the case study	136
4.12.2. Numerical results	136
4.13. Ferritic steel 35NiCrMo16 [TAL 15]	139
4.13.1. Context of the case study	139
4.13.2. Numerical results	139
4.14. Ferritic steel XC18 [TAL 13a]	141
4.14.1. Context of the case study	141
4.14.2. Numerical results	141
4.15. Phase transformation in titanium alloys Ti6Al4V [LON 09]	143
4.15.1. Context of the case study	143
4.15.2. Particular model features	143
4.15.3. Numerical results	144
Chapter 5. MM Damage-Plasticity Models	147
5.1. MM models based on the GTN approach	148
5.1.1. Damage in the 2M1C model based on the GTN approach	149
5.1.2. Damage in the 2M2C model based on the GTN approach	150
5.2. MM models coupled with CDM theory	151
5.2.1. 2M1C model “Strain Equivalence”	153
5.2.2. 2M2C model “Strain Equivalence”	154
5.2.3. 2M1C model “Energy Equivalence”	156
5.2.4. 2M2C model “Energy Equivalence”	157
5.3. Two plastic mechanisms combined with a damage mechanism	159

5.4. MM models taking into account volume change (CDM theory)	162
5.4.1. 2M2C model for compressible materials, CDM theory	165
5.4.2. MM models for compressible materials, CDM theory, two damage variables	167
5.5. Damage behavior of mortar-rubber aggregate mixtures	167
Chapter 6. Finite Element Implementation	171
6.1. Implementations of particular models	171
6.1.1. Basic version of the 2M1C model	172
6.1.2. β models	175
6.2. Creep–plasticity interaction in a notched specimen	183
6.3. FE analysis of plane forging of polycarbonate specimens	184
6.4. FE simulation of bulging of a 304SS sheet	188
6.5. FE simulation of PA6 notched specimens	189
6.6. Finite Element codes	198
6.6.1. ZeBuLoN: explicit integration	198
6.6.2. ABAQUS: explicit integration	199
6.6.3. ANSYS: explicit integration	206
6.6.4. ZeBuLoN: implicit integration	214
6.6.5. ABAQUS: implicit integration	216
6.6.6. ANSYS: implicit integration	233
Bibliography	253
Index	265